

Performing Arts Division -Technical Support Unit

Ngau Chi Wan Civic Centre

2/F & 3/F, Ngau Chi Wan Municipal Services Building, 11 Clear Water Bay Road, Kowloon, Hong Kong Phone 852-2325 1970 Fax 852-2320 2684

CONTACTS

Zoe TANG

Senior Manager (Kowloon East) Direct Line 852-2329 7735

Doris FUNG

Manager (NCWCC) **Direct Line** 852-2726 3576

Karen LAU

Resident Technical Manager (Kowloon) **Direct Line** 852-2329 7135 Fax Line 852-2320 2684

GENERAL SET-UP

The Theatre operates on a 'bare-walls' policy. That is, all equipment is normally set-up and struck within booking period. Hirers are reminded to allow sufficient preparation time to hang theatre masking, all rig overhead stage lighting and set up sound system. Check with our Technical Manager for any other equipment and technical enquiry.

Ngau Chi Wan Civic Centre - Theatre **FULL** Technical Information

V. 2024.10.21 Page 1 of 8





The Ngau Chi Wan Civic Centre Theatre traditional proscenium theatre designed and fully equipped for staging Chinese Opera, Dance, Drama, Musicals and variety performances.



DIRECTIONS

MTR: Kwun Tong Line, Choi Hung Station, Exit B

Freeway:

Choi Hung Interchange → Lung Cheung Road / Kwun Tong Road / Clear Water Bay Road / New Clear Water Bay Road

LOADING

Loading Shutter at tail board height: 3.00 x 3.00m (W x H)

Hoist System with maximum loading 500kg

Passenger lift:

Door: 1.10 x 2.10 m (W x H)

Inside: 2.30 x 1.90 x 1.70 m (H x W x D)

STAGE ENTRANCE

From Building Fover by Passenger lift.

PARKING



V. 2024.10.21 Page 2 of 8

AUDITORIUM



Seating Capacity: 354

PROSCENIUM

Structural Opening 9.40 – 5.28m (W x H)

STAGE WIDTH

Main stage width	13.51m
Centerline to stage left wall	6.99m
Centerline to stage right wall	6.52m

STAGE DEPTH

Rear of Proscenium to rear-stage shutter	10.80m
Rear of Proscenium to Black Backcloth (Bar 35)	9.30m
Rear of Proscenium to Cyclorama (Bar 34)	9.20m
Rear of Proscenium to the edge of the trap door	3.70m
Rear of Proscenium to forestage apron on centre line	2.40m

STAGE HEIGHT

Clearance under fly floors	7.83m
Clearance under grid	12.70m
Maximum counterweight bar flying height	12.10m
Above Auditorium	1.00m

FORESTAGE / ORCHESTRA PIT

Not available

STAGE FLOOR

Flat black surface – 6mm hardboard	
1 trapdoor at CS	2.07 x 1.08m (W x D)
Dip traps full depth of stage	

SIDE STAGE

Opening SL	8.50 x 2.60m (D x H)
Opening SR	5.30 x 2.60m (D x H)
Side stage area SL	4.00 x 8.50m (W x D)
Side stage area SR	2.50 x 5.30m (W x D)
Lightweight suspension grid	
2 self-sustaining fixed bar for side masking	9.90m (L), SWL 200kg

http://www.lcsd.gov.hk/en/tech/

V. 2024.10.21 Page 3 of 8

REAR STAGE

Ni

The fire shutter is treated as a safety curtain by FSD and cannot be obstructed by scenery, equipment or stage wagon in production.

STORAGE SPACE

Store area at side stage with limited space.

CROSSOVER

At rear of stage

RIGGING

House Curtain (Light Grey) fly in/out

Rigging System

Double purchase counterweights

Winch sets (Bar no. 4, 11, 14, 18, 23, 27 & 28)

Fixed Track (Bar no. 35)

Side Legs

Bar diameter (generally) Bars distance (generally)

Capacity (generally)

Bar length – 10.20 m with obstruction to side bars


Bar W1 carries the house curtain

Bar W27 carries the cyclorama lighting bar

Bar 34 carries cyclorama cloth

Bar 35 carries the black rear curtain

Side Bars



Motorized

27

7 (For rigging lighting equipment only)

1

7 per side

48mm 0.20m

0.20111

250kg SWL

1 per side

STAGE EQUIPMENT

Stage Drape	rv
-------------	----

Black masking	legs	14	flat	1.50 x 6.25m	
	borders	4	flat	10.20 x 2.50m	
	half tab	2	fullness	6.00 x 6.00m	Fixed installation on Bar 16 (mid curtain)
	black curtain	1	flat	11.2 x 7.15m	Fixed installation on Track T35 (rear curtain)
	side masking leg	16	flat	1.50 x 7.22m	Side Masking
Cyclorama		1	flat	10 x 6.35m	Bar 34 (general rig)

Orchestra Riser Wenger Trouper®

Aluminum frame platform.

Chair rails and guard rails available.

No drilling or painting.

2.40 x 1.20m (W x L) 203mm(H) 6 Sets 407mm(H) 6 Sets

Choir Riser (3 steps) Wenger Tourmaster 5 Sets (For approx. 60 persons)

Acoustic Shell Wenger Travelmaster 1 Set (5 acoustic shells)

Musician Chair 60

High Stool 2

Music Stands 50

/. 2024.10.21 Page 4 of 8

Dancing Flooring Black/Grey reversible for main stage

for dance show only (Please reserve time to lay the tiles during booking time)

(8.5 x 6.5m, for Cantonese Opera and Operatic **Stage Carpet** Green

Songs concerts only)

Concert Grand Piano Kawai GS-100 Instrument

> Timpani 1 set 4 sizes (23", 26", 29", 32") (extra charges incurred)

Chinese Timpani 1 set

Lift and Ladder

Aerial lifts operated by competent person & prior approved by venue management only.

DRESSING ROOM

Level 2 (Stage) 2 for 2 seats 2 for 10 seats

All dressing rooms are fitted with private shower

Quick change facilities can be temporary arranged when

required.

RUNNING WARDROBE

Not available.

Steamer, Irons & boards upon request from Resident

Stage Management

LIGHTING ETC Sensor 3 Digital ThruPower Dimmer 3kW Dimmer

Dimmer room located at 3/F

ETC GIO, with full backup control facilities, controllable of maximum 2048 circuits, located in **Control Board**

Lighting Control Room at rear of Auditorium.

Houselight Dimmer controlled. Controlled independently or via lighting control board.

Circuit 124 x 3kW production lighting circuits, fixed wiring type, circuits are terminated to True1

socket outlets respectively on the production lighting boxes, distributed at various locations

124

throughout the Stage and lighting bridges.

Additional Power

1 set 63Amp 3-phase CEE form socket, located in Stage Right wall for temporary cable

connection.

Connection must be conducted by a local registered electrical worker.

Hirer shall supply adequate circuit protective devices for all bring in electrical

installation.

Front of FOH Lighting Bridge no.1, 6.87m throw at 39.9 degree

Position

FOH Lighting Bridge no.2, 9.17m throw at 36.4 degree (apron)

House

Source 4 15°-30° **Profile** 750W **ETC** 16 **FOH Bridge** 270W ETC FOH Bridge

Source Four LED Series 12 2 Lustr Profile 15°-30°

750W Source 4 25°-50° 24 ETC Stage

Source 4 25°-50° 750W ETC 8 Lighting Slot 305W Source Four LED Series Sidelight towers ETC

3 Lustr X8 Zoom 25°-50°

7. 2024.10.21 Page 5 of 8

Fresnel	1kW 1kW 167W	Selecon Selecon ETC	Compact Compact Source Four LED Series 2 Lustr Fresnel	3 4 24	FOH Bridge Stage Stage
Cyclorama	133W	ETC	ColorSource CYC	5	Top (Bar W27)
Light Ground Row	133W	ETC	ColorSource CYC	5	Bottom (On Floor)
LED Automated Lighting	270W	Highend	SolaFrame 750	4	Fixed Installation at Lighting Slot
Ligiting	430W	ETC	Halcyon Gold	6	Stage

LED Automated Lighting requires time for setup and programming. Venue provides general operations and pre-programmed effects only. Hirers shall supply their programmer for designer programming and operation.

LED Spot	Follow	400W	Ushio	Sai-500		2	Auditorium Bridge
Smoke	Generato	or	Look Solutions	Viper NT		2	
Strobe	Light	3kW	Martin	Atomic 3000		2	
UV Lig	ht	120W	Wildfire	VioStorm VS	-120	2	FOH Bridge
Other		Side light tower Tower equipment * = Height the		4(top) 3 2 1 (bottom) from the centr	ETC LED Series Zoom 25°-50° e of lens to the	s 3 Lustr X8 s 3 Lustr X8 s 3 Lustr X8	1600mm* 1170mm* 740mm* 340mm*
		High Stand Floor Stand Music stand ligh	t (Cabled)	Doughty Sha Combo Stand Kupo 355 Un Floor Stand	d G203501	6 12 20	
Spotlig	Gobo Holo ght Applic ource Fou	able	<u>Iris</u> Qty. 10	<u>Holder</u> <u>Qty.</u> 15/15	<u>Holder</u> <u>Type</u> A/B	<u>Gobo</u> <u>Size</u> 100/86mm	<u>Image</u> <u>Size</u> n 68-75/65mm

Supply of above equipment subject to availability on receipt of a lighting plan.

Equipment availability does vary slightly according to equipment conditions and maintenance. Check with Technical Manager for any updates.

<u>Hirer will be provided with basic lighting only, from available hung equipment, if technical preparation time is less than 2 hours in the booking.</u>

All brought-in "Electrical and Stage Lighting Equipment" to be used in LCSD PA venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations". Please contact the venue management for any electrical safety concern. Website reference:

https://www.emsd.gov.hk/en/electricity_safety/index.html

V. 2024.10.21 Page 6 of 8

SOUND Sound System	L-Acoustics Sound System A10i Wide (Upper/Mid) & A10i Focus (Lower) X8 5XT X8 KS21i Soundcraft Vi 2000 mixing console with 32 Mono inputs, 1 Main	3 (Each side) 1 (Center Fill) 6 (Front Fill) 17 (Surround Speaker) 4 (Subwoofer) stereo output, 8 AUXs,
Console	8 Group outputs, 8 Matrix outputs	·
Microphone tie line	Both side of the stage	20 (total)
Microphone	Shure Beta 57A Shure Beta 58A Shure MX412 Neumann KM84 Neumann KM184 Sennheiser MKH816P48U-3 gun mic AKG C535 EB AKG C414 Crown PCC-160 DPA VO 4099 Lo DPA 2011C	10 6 2 4 4 4 3 4 4 4 4 4
Wireless Microphone	Shure ADX1M Bodypack transmitter (with Shure TL47 Lavalier) Shure ADX2 Handheld transmitter (with Beta87A Capsule) Max. 8 units with a minimum booking of 2 sessions (extra ch	8 8 narge incurred)
Stage Monitor	L-Acoustics X12	8
CD	Tascam SS-CDR250R Tascam SS-R250N	4 2
Accessories	BSS AR 133 Direct Box	4
DLP Projector	Panasonic PT-RZ21K	1
LED surtitle board system	Horizontal LED Display Boards (Incur extra charge)	2 sets
	Location:	Under lighting slot of the proscenium on both sides
	Display Text:	4 rows per display
	Character Support:	Traditional Chinese, Simplified Chinse and English
	Size of LED board:	150 x 75 cm (W x H)
	Default font color : White	
	The system will display in four lines per page. Each line for maximu approximate 20 English alphabets, include punctuation mark.	m 13 Chinese words or
	Surtitle input and stored in Microsoft® Word (*.docx) or text (*txt) file	format.

V. 2024.10.21 Page 7 of 8

The control computer was set inside control room at the back of auditorium. Display on ALL boards will be identical.

LED board is set up within booking period when two sessions or more are booked. Setup time normally requires one hour.

COMMUNICATION

Stage managers control panel at stage left

Cue light system (3pcs.)

One channel intercom system for stage, lighting and sound

Two channels intercom system (only for the rehearsal sessions)

Paging and show relay system

Close Circuit TV system

Production desk can be set at the middle of the stall upon request

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal

V. 2024.10.21 Page 8 of 8

POOLED LIGHTING EQUIPMENT LIST For Production with a Lighting Designer

Profile	750W	ETC	Source Four Zoom 25°-50°	18
Fresnel	1kW	Selecon	Compact	6
Cyclorama Light	133W	ETC	ColorSource CYC	2
Par Light	1kW 1kW 750W	Strand Strand ETC	Par 64 CP60 Par 64 CP61 Source Four ParNel	10 10 6

Equipment on this list allocated on a <u>first come first served</u> basis on presentation of a complete lighting plan.

Pool equipment cannot be reserved for any pending design.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal

	EQUIPMENT LIST vith a Sound Designer	
Speaker	JBL EON Power 10 YAMAHA MSP3 L-Acoustics X8	1 2 2
Microphone	Shure SM58	3
CD Player	Tascam CD-450	2
LCD monitor	JVC LT-19A1 LCD TV SWIT S-1093F (9" LCD Monitor)	1 1
DVD	Panasonic DMR-EH59	1 (extra charges incurred)

Equipment on this list allocated on a <u>first come first served</u> basis on presentation of a complete production audio design.

Pool equipment cannot be reserved for any pending design.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal