

Performing Arts
Division –
Technical Support
Unit

Hong Kong City Hall

5 Edinburgh Place, Central, Hong Kong Phone 852-2921 2840 Fax 852-2877 0353

CONTACTS

Joyce LAM

Senior Manager (City Hall) Direct Line 852- 2921 2888

Wendy TANG

Manager (City Hall) Hiring Management Direct Line 852- 2921 2835 Fax Line 852- 2524 5898

852-2877 0353

Sheila TSANG

Resident Technical Manager (City Hall) sheilatsang@lcsd.gov.hk Direct Line 852- 2921 2802 Fax Line 852- 2537 6307

GENERAL SET-UP

The Concert Hall operates on a 'barewalls' touring policy. That is, all equipment is normally set up and struck within the booking period. Hirers are reminded allow to sufficient preparation time to hang masking and set up all stage lighting and audio equipment.

Check with our Technical Manager for any other equipment and technical enquiry.

Hong Kong City Hall – Concert Hall FULL Technical Information

V. 2025.08.15 Page 1 of 9





The Concert Hall is designed primarily as a symphony hall and acoustically and in other respects best suited for performance of music.

The Concert Hall is also suitable for Drama, Dance and Chinese Opera productions when the overhead sounding boards being folded and withdrawn upward to allow the use of grid and suspension bars for normal stage lighting and scenery drops.

DIRECTIONS

MTR

Tsuen Wan Line or Island Line, Central Station, Exit K Airport Express or Tung Chung Line, Hong Kong Station, Exit A

Freeway (From W to E): Connaught Road Central → Edinburgh place (turn left on City Hall Wilson Car Park)

Freeway (From E to W):

Connaught Road Central →
Connaught Road Place (turn right on Jardine House) →
Connaught Road Central →
Edinburgh place (turn left on City Hall Wilson Car Park)



LOADING

Rolling gate at backstage entrance left:

2.80 x 3.05m (W x H) Slide door to stage: 2.50 x 2.66m (W x H)

STAGE ENTRANCE

Backstage entrance

PARKING

Permit required



V. 2025.08.15 Page 2 of 10

AUDITORIUM



Total Seating: 1,430 Front Stalls: 578 Rear Stalls: 465 Balcony: 387

Extension stage edge. Formed by removal of Seats at Row A & B which will reduce 59 seats.

Orchestra Pit. Formed by removing forestage traps Capacity of 10-15 Formed by removal of musicians. Seats at Row A & B which will reduce 59 seats.

CONCERT MODE (SOUND CANOPY LAYOUT) PROSCENIUM

Structural Opening 12.00 x 9.00m (W x H)

STAGE WIDTH

From centre line to SR and SL (down stage) 9.30m From centre line to SR and SL (up stage) 7.35m Extension stage

(DS) 19.00m (Removal of 59 seats)

(US) 15.00m

STAGE DEPTH

Rear of safety curtain to Choir stalls 6.40m Choir stalls to forestage edge at centre 8.80m Choir stalls to forestage edge at SL or SR 8.05m

Choir stalls to extension stage edge 10.70m (Removal of 59 seats)

STAGE HEIGHT

9.80m To canopy down stage To canopy up stage 7.20m Above Auditorium 0.70m

THEATRE MODE (PROSCENIUM LAYOUT) **PROSCENIUM**

Structural Opening 12.00 x 5.00-5.60m (W x H) Adjustable proscenium opening with Teaser

STAGE WIDTH

From centre line to SR and SL (down stage) 9.30m From centre line to SR and SL (up stage) 7.35m

Extension stage 19.00m(Removal of 59 seats)

STAGE DEPTH

Rear of safety curtain to Choir stalls 6.40m Choir stalls to forestage edge at centre 8.80m Choir stalls to forestage edge at SL or SR 8.05m

Choir stalls to extension stage edge 10.30m (Removal of 59 seats)

STAGE HEIGHT

To grid level 15.85m To flying bars 14.00m Under fly galleries 10.80m Above Auditorium 0.70m

FORESTAGE / ORCHESTRA PIT

V. 2025.08.15 Page 3 of 10

ORCHESTRA PIT

Formed by removal of Seats at Row A & B which will reduce 59 seats.

Dimensions 18.97 x 1.48-1.93 x 1.10m (W x D x H)

Capacity 10 – 15 musicians

Pit setup provision with conductor podium, chairs, stools, music stands, and music lights

EXTENSION STAGE

Seats at Row A & B have to be removed when the extension stage is used.

There will be a reduction of 59 seats.

Dimensions 18.90 x 1.9-2.1 x 0.70m (W x D x H)

CHOIR STALL

Fixed choir stalls behind stage platform, capacity for 60 choir

3.00m deep with front rail 2.85m above stage

STAGE FLOOR

The surface of the stage consists of flat-strip timber planks on 500kg/m² SWL concrete, smooth but not waxed or polished. No nails or screws allowed.

Trap - Not available

SIDE STAGE

Very limited off platform / stage area

REAR STAGE

Not available

The fire shutter is treated as a safety curtain by FSD and cannot be obstructed by scenery, equipment or stage wagon in production.

STORAGE SPACE

Very limited off stage area

CROSSOVER

Corridor behind stage

11070 BSS 11070 BSS 11070 BSS 11070 BSS 110741 18875 1180 17 16 15 14 13 12 11 10 1 2 3 4 5 6 7 8 9 2684

24

RIGGING (For Theatre mode only)

House Curtain (Sliver) manual fly or motor travel

Bar 1, fly in and out manually and draw left and right electrically at varying speed

BP Screen

Bar 24

Stage Lighting Bar

Standard lighting bars
LED Cyclorama lights
Bar 4 and 13
Bar 17

Rigging System

Single purchase counterweights

Counterweight frame located at stage right

Bar length 15m (except Bar no. 2, 4-6, 8-13 are 16m Bar no. 19-24 are 14m long)

Bar diameter 60mm (upper bar) 48mm (lower bar)

Bars distance (generally) 0.20m

Capacity 0.2011

250kg SWL

Pinrail None Side Bars None

V. 2025.08.15 Page 4 of 10

V. 2025.08.15					Page 4 of 10	
Point Hoists				None		
STAGE EQUIPM	MENT					
Stage Drapery						
Black masking	leg	2	flat	2.50 x 7.00m	General rig (W x H)	
3	3	4		3.50 x 7.00m	General rig	
		2		4.50 x 7.00m	General rig	
	border	_ 1		17.00 x 2.50m	General rig	
	20.40.	2		16.00 x 2.50m	General rig	
	half tab	2		8.00 x 7.00m	General rig, as mid curtain for	
	nan tab	-	iidt	0.00 X 1.00111	general rig	
	tab	2	fullness	15.00 x 7.00m	General rig	
					er. It can be used as flat or semi-	
		lothes by tying			i. It dan be used as hat or semi	
White Diestic Co	, al a wa wa a	4	flat	11.00 × 0.00 ==	Cananal via	
White Plastic Cy	ciorama	1	flat	14.00 x 8.00m	General rig	
Black gauze		1		14.00 x 7.50m		
White gauze	- (F ₀ 1 / F	1		14.00 x 7.50m	(11)	
Projection scree	n (Front / Ba	ick) 1		4.00 (W) x 3.00m		
				On stand or hang	on bar (Theatre Mode only)	
Orchestra Riser Aluminum frame platform. 2.4 x1.2m (W x D) 6 203mm(H) 6 407mm(H) 6 610mm(H)				r painting.		
Choir Riser (3 o	Choir Riser (3 or 4 steps) Wenger Tourmaster for approx. 80-90 persons					
Orchestra Chai	r	120				
Music Stand		70				
Conductor's Po (can be combine steps podium)	e combined into 2- 1 1.22 x 0.97 x 0.18m (L x W x H)			,		
Conductor's Stand		1				
High Stool 5		5				
Ceremony Chai	ir	12				
Podium		1		0.76 x 0.45 x 1.2	22m (W x D x H)	
Table		5		1.22 x 0.76 x 0.7	'4m (W x D x H)	
		Black for ma (<u>Please allo</u>	main stage Illow time to lay the ties during booking time)			
Stage Carpet for Chinese Ope	era only	Green	2	5.50 x 5.50m (V	V x D)	
Instruments	Concert Grand Piano. (incur extra charge) Harpsichord (incur extra charge)		2	Steinway & Sons	s D-274	
			1	William Dowd Bo	oston 1966	
			•	(Share with HKC		
	Harp	a sharge)	1	Lyon & Healy Ha		
	(incur extra	a charge)	1	(Share with The		
	Timpani	a Griarye)	1 set of 4		EN 2 (23", 26", 29", 32")	
	(incur extra	a charge)	1 351 01 4	(Share with Thea		
	(IIIOUI EXII	a Griarye)		(Onale with Tiles	au o j	

V. 2025.08.15 Page 5 of 10

Up-right Piano 2 (Located at dressing rooms C2 & C5)

Lift and Ladder

Hydraulic lifting platform (7.00m Height) 1 operated by competent person & prior approved

by venue management only

Counterweight Available as requested

s

DRESSING ROOM

First floor C1: accommodates 15-20 persons

C2: accommodates 5-8 persons **C3:** accommodates 3-5 persons

Second floor C4: accommodates 15-20 persons

C5: accommodates 5-8 persons **C6:** accommodates 3-5 persons

All dressing rooms fitted with private toilet and shower

(C3 with no shower)



RUNNING WARDROBE

Washing machines, dryers, located at dressing room C3

Sewing machines, irons & boards and steamers can be loaned from Stage Management Department

LIGHTING

Dimmer ETC Sensor3 dimmer. Total 144 nos.

3kW 130 nos. 5kW 14 nos. Locating at back stage corridor.

Control Board ETC Gio, with full backup control facilities, EOS Family OS operating software, located in

Lighting Control Room at side stage of Stage Left.

Remote Control ETC – wireless remote control.

Houselight Dimmer controlled. Controlled independently or via lighting control board.

Circuit 130 x 3kW production lighting circuits distributed at various locations throughout the Stage

and lighting bridges. Another 12 x 3kW and 2 x 5kW production lighting circuits located in dimmer room at back stage. Terminated to 15A or 32A socket outlets to UK standard on the

production lighting boxes.

Additional Power

220/380 Volt; 3-phase/4 wire, 32A/phase and 63A/phase, located in US Left side stage wall

c/w and dimmer room.

Connection must be conducted by a local registered electrical worker.

Hirer shall supply adequate circuit protective devices for all bring in electrical

installation.

13A wall-mounted socket outlets at UK standard are provided on the stage.

Front of FOH Lighting Bridge no.1, 17.13m throw at 42.65 degree

House FOH Lighting Bridge no.1, 15.80m throw at 47.60 degree (Apron)

Position FOH Lighting Bridge no.2, 19.71m throw at 36.20 degree

FOH Lighting Bridge no.2, 18.13m throw at 39.95 degree (Apron)

Circle Rail, 17.85m throw at 16.97 degree

Circle Rail, 15.94m throw at 19.08 degree (Apron)

Profile 750W ETC Source Four Zoom 15 -30 4 Canopy Light Bar

750W ETC Source Four Zoom 25 -50 2 Canopy Light Bar

V. 2025.08.15 Page 6 of 10

	750W	ETC	Source Four Zoom 15 -30	4	Left & Right Box
	750W 750W	ETC ETC	Source Four Zoom 15 -30 Source Four Zoom 15 -30	24 12	Under Bar Ceiling I & II Circle Front
Fresnel	300W	ETC	Source Four LED Series 3 Lustr X8 Fresnel	8	Canopy Light Bar
	300W	ETC	Source Four LED Series 3 Lustr X8 Fresnel	22	Bar 4, 13
LED Automated Lighting	550W	Robe	T1 Profile	6	Left & Right Box Under Bar
Cyclorama light	RGBAL 148W	Chauvet	Ovation CYC 1 FC	7	Top (with yoke) (Bar 17)
Ground Row	RGBAL 148W	Chauvet	Ovation CYC 1 FC	7	Bottom (without yoke)
Follow Spot	800W	Robert Juliat	ARTHUR 10 -14 LT LED	2	At back of auditorium in balcony
Canopy light	750W	ETC	PARNel	24	Fixed on canopy and used for concert mode
Work Light (Flood light)	1kW 500W			2 6	Canopy Light Bar 2 SL, 2SR, 2 FOH
Smoke generate Strobe Light UV light	or			As requ	ired from pool stock ired from pool stock ired from pool stock
Other	Side light tower 8 (Pre-rigged and share with Theatre)			8	
Tower equipment	t setup:	5 (top) 4 3 2 1 (botto	As request ETC Source Four Zool 1kW Selecon Rama Fr 1kW Selecon Rama Fr m) ETC Source Four Zool	esnel esnel	220cm* 180cm* 135cm* 90cm*
	* = Height t	•	from the centre of lens to th		45cm*

^{* =} Height the equipment from the centre of lens to the floor

Supply of above equipment subject to availability on receipt of a lighting plan.

Equipment availability does vary slightly according to equipment conditions and maintenance. Check with Technical Manager for any updates.

Hirer will be provided with basic lighting only, from available hung equipment, if technical preparation time is less than 2 hours in the booking.

All brought-in "Electrical and Stage Lighting Equipment" to be used in LCSD PA venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations (2020 Edition)". Please contact the venue management for any electrical safety concern. Website reference: https://www.emsd.gov.hk/en/electricity_safety/index.html

SOUND

Sound System Main central cluster:

d&b Ti10L 8
Left and right:

 d&b F-1222
 3 (on each)

 d&b B1-SUB
 2 (on each)

 d&b Ci-45
 1 (on each)

V. 2025.08.15 Page 7 of 10

	Balcony left and right:		
	d&b audiotechnik Qi-1	4	
	Stage front: d&b E3	4	
	dab E5	7	
Main Control	Digico Quantum 852 mixing console		
Console	Mono inputs	32	
	Stereo inputs	8	
	Aux outputs	12	
	Bus outputs	12	
	Matrix outputs	8	
	Control room at the back of auditorium		
Microphone	At main reflector	6	
tie line	At hanging bar	3	
	Stage front	12	
	Stage left with multi-pair cable	16 16	
	Stage right with multi-pair cable	10	
Accessory	Lexicon 480L digital effect system	1	
Electronics	Lexicon PCM 96SUR-D digital effect processor	2	
(Pre-aligned, not	5		
loose equipment)			
Microphone	B&K 4003 A-B stereo recording microphone system	2	
	Crown PCC160	3	
	AKG C414B-ULS	4	
	Neumann KM183	2	
	Neumann KM184	6	
	Sennheiser MD421-II	2	
	Shure Beta 57	2	
	Shure MX412	2	
	Shure Beta 58	5	
	Shure SM 57	4	
	Shure PG 58	4	
Wireless	Sennheiser SKM 5200-II hand-held type	8	
Microphone	Sennheiser SK 5212-II body-pack type	8	
(incur extra charge)	Max. 8 units with a minimum booking of 2 sessions	-	
,			
Stage Monitor	d&b audiotechnik M6	10	
	Meyer Sound UP-JUNIOR	2	
CD	Tascam CD-6010 CD player	2	
CD Recorder	Tascam SS-CDR250N	2	
OD Necoldel	14364111 00-0D1123011	2	
Multimedia	Christie DHD1075-GS (10,000 ANSI Lumens)	1	
Projector	(Control panel at left box of left promenade)		
(incur extra charge)			
Video Monitor	SWIT S-1093F 9"Full HD Broadcast LCD Monitor	4	
A	Direct Payer		
Accessory	Direct Boxes		
	Microphone stands		
	Sub snakes		
	Cables and adapters		

V. 2025.08.15 Page 8 of 10

4K Video Filming &	Matrox Monarch EDGE	1
Image Processing	4K video encoders and decoders	
System	Panasonic AW-UE150 4K Integrated PTZ Camera	5
(Incur extra charge)	BlackMagic ATEM 4 M/E Broadcast Studio 4K	2
	BlackMagic ATEM 1 M/E Advanced Panel	1
	BlackMagic 4K 12G Hyperdeck SSD video recorder	6

COMMUNICATION

Stage manager control panel at stage left

Dual channels production communication systems for stage, lighting and sound

Paging and show relay system

Cue light system

Close Circuit TV system

Production desk can be set at the middle of the stall

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal

V. 2025.08.15 Page 9 of 10

POOLED LIGHTING EQUIPMENT LIST for Productions with a Lighting Designer					
loi i roddotioi	10 With a Lig	nting Beorginer		<u>Theatre</u>	Concert Hall
Profile	750W	ETC	Source Four Zoom 25 - 50	10	8
	750W	ETC	Source Four Zoom 15 - 30	25	30
	1kW	G&E	Par 64 (CP61)	20	15
	300W	ETC	Source Four LED Series 3 Lustr	2	8
Fresnel	2kW	Selecon	Arena Theatre F	3	2
	Lens	ETC	Source Four LED Series 3 Lustr (Fresnel Adaptor)	8	8
Music light				70	30
Light stand				4	4
Floor stand				10	10
Light tower			1.90m height	4	4
Gobo holder		Source Four	A size B size		54 24
Iris		Source Four			28
Strobe light		Martin	Atomic 3000 DMX	2	2
UV Light	400W	Wildfire	LT-400F	2	2
Smoke machine		Viper	NT	2	2

Equipment on this list allocated on a <u>first come first served</u> basis on presentation of a complete lighting plan.

Pool equipment cannot be reserved for any pending design.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal

V. 2025.08.15 Page 10 of 10

POOLED SOUND EQUIPMENT LIST for Productions with a Sound Designer

Microphone pool	Neumann KMR-82i shotgun	4
	AKG D112	3
	AKG C411	4
	Shure 565SD	2
	Shure Beta 87	2
	Shure SM94	3
	DPA 2011A	8
	DPA 4099	8

Equipment on this list allocated on a <u>first come first served</u> basis on presentation of a complete production audio design.

Pool equipment cannot be reserved for any pending design.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment. All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal