

Performing Arts
Division –
Technical Support
Section

Ko Shan Theatre

77 Ko Shan Road Hung Hom Kowloon, HK Phone 852- 2740 9222 Fax 852- 2781 4783

CONTACTS

Doris FUNG

Senior Manager(KW) Direct Line 852- 2740 9219

Ming KWOK

Manager(KST)H&M Direct Line 852-2334 6378

Karen LAU

Resident Technical Manager(K) Direct Line 852- 2330 4761 852- 2329 7135 Fax Line 852- 2365 0503

GENERAL SET-UP

The Ko Shan Theatre operates on a basic setup policy. That is, all equipment has a prerigged position at the start of bookings. Hirers reauiring move remove or equipment must do so (and reinstate it) within their booking period.

Check with our Technical Manager for any other equipment and technical enquiry.

Ko Shan Theatre – Theatre FULL Technical Information

V. 2025.07.21 Page 1 of 8





Ko Shan Theatre is a traditional proscenium theatre, but without a full fly tower, which limits its technical abilities. Primary use is for Chinese Opera and Chinese Dance. Secondary use is for Drama, Concerts and Assemblies.

DIRECTIONS

MTR:

Kwun Tong Line, Ho Man Tin Station, Exit A2

Tuen Ma Line, To Kwa Wan Station, Exit C


Tsuen Wan Line, Mong Kok Station, Exit B2 → Mini bus Routes No. 27M

Freeway (From S to N):

Hung Hom Cross Harbour Tunnel →
Hong Chong Road → Chatham Road
North → Pak Kung Street (turn right)
→ Ko Shan Road

Freeway (From N to S):

Boundary Street \rightarrow Waterloo Road \rightarrow Princess Margaret Road \rightarrow Fat Kwong Street \rightarrow Shun Yung Street \rightarrow Ko Shan Road



LOADING

Clearance of truck: 4.70m Steel Door Opening: 2.73 x 4.56m (W x H)



PARKING

Permit required

V. 2025.07.21 Page 2 of 8

AUDITORIUM



Total Seating: 1031

Stalls: 916 Balcony: 115

Major seats are disposed in a wide Stalls fan with seats in a shallow Balcony.

PROSCENIUM

Structural Opening 12.97 x 4.96m (W x H)
Adjustable proscenium opening with Teaser and Tormentor 12.00 x 5.00m (W x H) Max.

STAGE WIDTH


Centreline to stage right 8.48m
Centreline to stage left 8.48m

STAGE DEPTH

Rear of Proscenium to cyclorama on centreline	11.59m
Rear of Proscenium to cyclorama at sides	7.52m
Rear of Proscenium to cyclorama surround bar on	11.30m
centreline	
Rear of Proscenium to last full cross-stage bar	7.35m
Rear of Proscenium to forestage on centreline	3.42m
Forestage radius	13.00m
Rear of Proscenium to orchestra pit edge on	2.90m
centreline	
Orchestra pit radius	10.17m

STAGE HEIGHT

Clear under grid	7.00m
Maximum bar flying height	6.30m
Above Auditorium	1.00m



FORESTAGE / ORCHESTRA PIT

Formed by removing trap and lowering centre lift, maximum for 12 persons

Pit setup provision with chairs, stools, music stands, and music lights

STAGE FLOOR

Flat black hardboard
Trapdoors - None
Footlight trough and Dip sockets

V. 2025.07.21 Page 3 of 8

SIDE STAGE

 Stage Right
 4.69 x 4.92m (W x D)

 Stage Left
 6.09 x 4.82m (W x D)

REAR STAGE

Not Available

STORAGE SPACE

Limited space

CROSSOVER

Corridor behind stage

RIGGING

House Curtain (Violet) - festoon type

Rigging System

 Motor Bars
 7

 Bar Diameter
 48.50mm

 Stage Bar 3, 8, 14 & 19
 16.00m

 Bar 24
 14.00m

 Capacity
 250kg SWL

Bar 2 16.10m Capacity 150kg SWL

Forestage Bar B, C 11.00m Capacity 500kg SWL

 Motorized Lighting Bars
 5

 Bar 1, 6 & 17
 15.30m

 Bar 25 & 26
 10.00m

 Capacity
 500kg SWL

 Hand Winch
 9

 Wiper Track Bar 4, 5, 9, 10, 15, 16, 20 & 22
 27.50m

 Forestage Bar A
 13.00m

 Capacity
 250kg SWL

Fixed Height Overlap Curtain Track 3
Bar 7, 12 & 23 16.00m

Cyclorama Curved track 1
Bar 30 17.65m
Capacity 250kg SWL

 Hemp set (For Cloth Hanging Only)
 8

 Bar Diameter
 51.00mm

 Bar 11, 13, 18 & 21
 16.10m

 Bar 27
 11.50m

 Bar 28 & 29
 10.10m

 Capacity
 150kg SWL

Pinrail None

Side Bars None

Point Hoists

Page 4 of 8

					Page 4 of
None					
STAGE EQUIPMENT					
Stage Drapery					
Black masking leg	6	flat		3.00 x 6.25m	(W x H)
	2	flat		2.00 x 6.30m	
border	1	flat		18.00 x 1.80m	
	3	flat		18.00 x 1.50m	
	1	flat		16.00 x 1.55m	
	1	flat		16.00 x 1.20m	
half tab					A - 4st and a ard maid acceptain
naii tab	6	flat		9.00 x 6.90m	As 1 st , 2 nd , & 3 rd mid-curtain
Wrap round Black cyclora	ma 2	flat		9.60 x 6.25m	
Orchestra Riser				Wenger Portma	ster.
Aluminum frame platform.					
Chair rails and guard rails			ing.		
2.40 x1.20m (W x L)	203	8mm(H) x 4			
	407	mm(H) x 4			
)mm(H) x 4			
Choir Riser (3 steps)	6			Wenger Tourma	aster
Musician Chair	60			Black	
Music Stand	20			Black	
Conductor Platform	1				
Conductor Music Stand	1				
Stool	5				
Podium	1				
Ceremony Chair	12			Red	
Dancing Tile	Black for main s	tage			
for dance show only			tiles durin	g your booking time	e)
,	(, , , , , , , , , , , , , , , , , , , ,		a , 	=/
Stage Carpet					
for Chinese opera only	Pale Green		2	13.00 x 3.50m	
for Crimese opera omy	rale Gleen		2	13.00 X 3.30111	
In a 4	Harialet Diama		4	l la sialat a i a a a V	
Instruments	Upright Piano		1	Upright piano Y	amana U1
	18" Chinese Dru	ım	1		
Lifting Platform	Upright UL-24		1	operated by cor	mpetent person
O. W	40 Els		00		
Stage Weight	12.5kg		20		
DDESSING DOOM					
DRESSING ROOM					
Level 1		persons			
		persons			
Level 2	Room 2, 3: 4	persons (ea	ch room)		
		persons	-		
Level 3		, persons (ea	ch room)		
20.0.0	, 5. 12	73,33,10 (00			

All dressing rooms at level 2 & 3 fitted with private and public toilet and shower

Quick change facilities downstage right and left.

V. 2025.07.21 Page 5 of 8

RUNNING WARDROBE

None.

Iron & board and steamer are available upon request.



LIGHTING

Dimmer 192 channels of ETC Sensor3 3kW dimmers locating in Lighting Control Room

Control Board grandMA3 Light 4096 outputs, with full back up control facilities, located in Lighting Control Room

Houselights Dimmer controlled. Controlled independently or via lighting control board.

Circuits 192 x 3kW production lighting circuits, fixed wiring type, circuits are terminated to 15A socket

outlets to UK standard respectively on the production lighting boxes, distributed at various

locations throughout the Stage and lighting bridges.

Additional

DSR: 220/380 Volt; 3-phase/4 wire, 160A/phase, c/w 160A clamping bus bar;

Power DSR: 220/380 Volt; 3-phase/4 wire, 63A/phase, c/w two 32A sockets for temporary cable

connection.

Conducted by the local registered electrical workers.

The hirer shall supply adequate circuit protective devices for your own electrical

installation.

13A wall-mounted socket outlets to UK standard are provided on the stage.

Front of House FOH Lighting Bar, 5.75m throw at 47 degree

Position FOH Lighting Bridge no.1, 11.00m throw at 38 degree

FOH Lighting Bridge no.1, 9.19m throw at 48 degree (Apron)

Profile	750W 750W 750W 750W	ETC ETC ETC ETC	Source 4 25/50 Source 4 15/30 Source 4 19 Source 4 10	7 50 5 18	
LED Profile	167W 185W	ETC ETC	Source 4 Lustr2 15/30 ColorSource Spot 25-50	26 6	
Fresnel	2kW 1kW 1kW	Strand Strand Strand	Patt 828 Cantata F Harmony F	2 18 36	
Parcan	1kW 750W	ETC	PAR 64 CP61 Source 4 PARnel	20 6	
LED Par	135W	Altman	AP-150	12	
LED Cyc. Light	334W	Chauvet	Ovation Cyc 3 FC	5	Electric Bar 26 (No. 5 Lx Bar)
LED Ground Row	334W	Chauvet	Ovation Cyc 3 FC	5	Bottom

V. 2025.07.21 Page 6 of 8

LED Moving Head	1kW	Robe	DL7S		2		
	430W	ETC	Halcyon Gold	d Ultra Bright	12		
LED Batten	210W	ETC	ColorSource	Linear2	6		
LED Follow Spot	600W	Robert Juliat	OZ-1169		2	Auditorium	Perch
Smoke Generate	or	Look Solutions	Viper NT		2		
Strobe Light	1.5kW	Anytronics	DeathStar		2		
UV light	40W 175W	Griven Wildfire	GR0101 VioStorm		4 2		
Gobo holder Spotlight Applic ETC Source 4 Pr		Gobo Hol <u>Qty</u> 20 / 20		obo Holder <u>Type</u> A / B	Gob <u>Siz</u> 100 / 86	<u>e</u>	Image <u>Size</u> 68-75 / 65mm
Other	Side light tower 712 x 5		712 x 558 x	2097 mm	8		
	Tower equipment setup: * = Height of the equipment		5(top) 4 3 2 1 (bottom)	1kW Strand Harmony F 1kW Strand Harmony F 1kW Strand Harmony F 1kW Strand Harmony F Empty		1067m	m* m*
	LED Music light RATstands Apollo Lig			Apollo Light	30		
Equipment available does vary slightly according to equipment conditions and maintenance. Check with							

Equipment available does vary slightly according to equipment conditions and maintenance. Check with Technical Manager for any update.

<u>Hirer will be provided with basic lighting only from available hung equipment, if technical preparation time is less than 2 hrs in the booking.</u>

All brought-in "Electrical and Stage Lighting Equipment" to be used in LCSD PA venues, shall meet the requirements of "Code of Practice for Electricity (Wiring) Regulations (2009 Edition)". Please contact the venue management for any electrical safety concern. Website reference:

http://www.emsd.gov.hk/emsd/eng/welcome/em_safety.shtml

SOUND			
Sound System	Meyer M1D	(main central cluster)	8
	Meyer MINA	(main left & right)	12
	Meyer ULRA-X42	(delay loudspeaker for balcony)	3
	Meyer MM-4XP	(front fill loudspeaker)	6
	Meyer 700-HP	(subwoofer loudspeaker)	2
Main Control Console		3, digital mixing console with 36 chan 12) in control room at rear of auditori	
Microphone	apron		9

V. 2025.07.21 Page 7 of 8

tie line	curtain line stage house 4 corners orchestra pit centre and rear auditorium catwalk (3 bridges) Multicore (16 channels) inlets at stage left, stage right, orchestra pit, and rear auditorium	7 24 8 8 6 4 sets
Accessory	Klark Teknik DN-500 compressor/ limiter/ expender	2
Electronics	Yamaha SPX-990	1
(Pre-aligned, not loose equipment)	TC Electronics M3000 Studio Reverb Processor	1
Microphone	AKG C-414 B-ULS AKG C-414 XLS AKG C-621E AKG C-418 AKG C-409 AKG C-419 Audio Technica ATM-73a Crown PCC-160 Crown PZM-30D DPA 4099 Neumann KM-184 Neumann KM-185 Neumann KMR-81i Neumann KMR-82i Sennheiser 421-II Shure Beta 57 Shure Beta 57 Shure Beta 87 Shure Beta 87 Shure Beta 91	1 4 2 4 2 4 2 4 2 3 3 4 1 3 4 4 4 3 8 2 2 1
Wireless Microphone	Sennheiser SK 2000-Dw wireless microphone (clip) Sennheiser SKM 2000 BK-Dw (hand-held) Max. 8 units with a minimum booking of 2 sessions	8 8
Stage Monitor	Meyer UPJ-1XP Meyer MJF-210 Meyer UMS-1P Meyer MJF-208	10 2 2 2
CD	Tascam-SS-CDR200	2
DVD Player	JVC SR-HD2700E Blu-ray player	2
Multi-media Equipment	Computer Controlled surtitles projection system: Horizontal bilingual surtitles or vertical Chinese surtitles Panasonic PT-RX110LB DLP Laser Projector w/ ET-DLE350 long zoom lens Panasonic PT-DW17K2 DLP Projector w/ ET-D75LE30 zoom lens	1 2 1
VIDEO FACILITIES		

V. 2025.07.21 Page 8 of 8

Rolled Projection 10.50 x 6.50M (W x H) Immediately DS of False Proscenium

Screen (Bar 4) 12' x 12' (W x H)

1

1

COMMUNICATION

Stage manager control panel at stage right

Dual channels intercom system with single/ dual channel(s) body-pack

Single channel wireless body-pack

Cue light system

Front-of-house paging/ Public address, Backstage paging/ Show relay system

Close Circuit TV

High Resolution camera and infra-red camera for stage house

system Infra-red camera for auditorium

CCTV at stage manager's desk, side stage left and right

CCTV at G/F left and right stalls lobby entrance and 1/F balcony foyer

Production desk Set at the centre of the stall upon request

EMERGENCY FOH ANNOUNCEMENT SYSTEM

UPS maintained FOH emergency announcement system with hand-held wired microphone and digital playback.

Prior to booking date, please confirm with Technical Manager for the availability of the equipment.

All required equipment will be set-up during the booking sessions; please allow adequate time for equipment set-up before performance or rehearsal.